


Valve Sealant

PART NO: PLI-200-HP-SEAL

PLI's SYNTHETIC VALVE SEALANT is a last line of defence in valve maintenance, i.e. a valve must be sealed at all costs to eliminate the need for an untimely shut down. Our valve sealant contains no PTFE-fillers, will not harden and is excellent for emergency seat renewal and low pressure sealing problems. It comes in various grades, but the standard grade is good for H₂S and CO₂ services. The 2010 product will be immiscible in condensate.

 PRESSURELUBE INTERNATIONAL		Pressure Lube International Pty Ltd A/NZ 17 088515117 Jackson Street, Bassendean Western Australia 6054 Telephone +61 8 9279 1200 Facsimile +61 8 9279 9929 www.pressurelube.com.au
ON LINE VALVE LUBRICATION & SEALING		
PRODUCT	VALVE SEALANT	
PART NO	PLI- 200-HP-SEAL	
BATCH NO		
MANUFACTURE DATE		
EXPIRY DATE		
SYNTHETIC VALVE LUBRICANT 100% SYNTHETIC NO FILLERS Protects against corrosion Resists H ₂ S, CO ₂ , Water, Acid - Brine Will not harden in valve	NOTE: NON HAZARDOUS GOODS PRODUCT CAN BE SHIPPED BY AIR	
APPLICATION Valve Sealant for Oil & Gas Industry	AUSTRALIA CONTACT Tel: +61-8-9379 1200 Fax: +61-8-9279 9929 PLI3154	

By using a unique combination of 100% fully synthetic oils and a propriety thickener, PLI HIGH PERFORMANCE VALVE SEALANT was formulated to provide a superior lubricating and sealing compound that is unsurpassed in performance.

There are no fillers such as clay, bentonite or soaps or PTFE PLI HIGH PERFORMANCE VALVE SEALANT does not rely on these fillers as bridging agents.

When injected into the valve, PLI HIGH PERFORMANCE VALVE SEALANT lubricates and seals with as much as 90 percent greater efficiency. PLI HIGH PERFORMANCE VALVE SEALANT will not harden in valve seats or lubrication channels thus eliminating frequent flushing of the valve and allowing for torque operation.

PLI HIGH PERFORMANCE VALVE SEALANT will resist washouts by crude condensate, water, gas, diesel, hydrocarbon acid, oil field brine, H₂S, CO₂ and is insoluble in water. It can withstand a wide temperature range form -60F to 500F.

BENEFITS

- 100% Synthetic
- Does not contain fillers
- Low friction coefficient
- Resistant to water washout
- Protects from corrosion
- Effective temperature range of -60°F to 500°F
- Protects against H₂S and CO₂

APPLICATION

PLI HIGH PERFORMANCE VALVE SEALANT can be applied using an air operated lubrication pump, a hand held grease gun or a volume bucket pump.

RECOMMENDED USERS

By Valve manufacturers, valve refurbishes, pipeline and wellhead companies, refineries and LNG plants.

PACKAGING

40Lb Pails (20 Ltr)

SAFETY DATA SHEET

Available for download from PLI website
www.pressurelube.com.au

Manufactured in the USA by Lubchem for PLI formulation.

